

Forestry Fog Nozzles

Features

- Maroon hard-coated barrel allows for easy identification
- Corrosion resistant plated
- Dual flow rate nozzles offer two straight stream and two fog patterns
- Combination fog and straight stream

Specification

- Maximum operating pressure: **600 PSI** (water only) at **70°F (21°C)**

| Size | Thread | GPM @ 100 PSI Straight Stream | | 6061-T6 Aluminum Part # |
|--------|----------|-------------------------------|------------------|--------------------------|
| | | 1st | 2nd | |
| 3/4" | GHT | 1-2 | 3-4 ¹ | FFN75GHT ¹ |
| 1" | NPSH | 12 | 25 | FFN100 ^{2,4} |
| 1-1/2" | NPSH | 25 | 70 | FFN150 |
| 1" | NST (NH) | 12 | 25 | FFN100NST |
| 1-1/2" | NST (NH) | 25 | 70 | FFN150NST ^{3,4} |



FFN75GHT



FFN100

¹ GPM @ 40 PSI

² FFN100 meets USFS 5100-239A and NSN 4210-01-165-6603

³ FFN150NST meets USFS 5100-107A and NSN 4210-01-167-1123

⁴ both nozzles conform to Forestry Service specification 5100-239C and 5100-107a

Forestry Grade Ball Shutoff Nozzles

Feature

- Hardcoated threads, acetal ball, and rigid inlet

Approvals

- NFPA1964 compliant
- FSS specification 5100-238

Specification

- Maximum operating pressure: **600 PSI** at ambient temperature **70°F (21°C)**

| Size | Thread | Waterway | Anodized Aluminum Part # |
|--------|----------|----------|--------------------------|
| 1" | NPSH | 3/4" | FBSO100S |
| 1-1/2" | | 1" | FBSO150S |
| 1" | NST (NH) | 3/4" | FBSO100F |
| 1-1/2" | | 1" | FBSO150F |



Forestry Grade Ball Shutoff Pistol Grips

Features

- Hardcoated threads, acetal ball, and full time live swivel inlet

Approvals

- NFPA1964 compliant
- FSS specification 5100-238

Specification

- Maximum operating pressure: **600 PSI** at ambient temperature **70°F (21°C)**

| Size | Thread | Waterway | Anodized Aluminum Part # |
|--------|----------|----------|--------------------------|
| 1" | NPSH | 3/4" | FBSO100S-PG |
| 1-1/2" | | 1" | FBSO150S-PG |
| 1" | NST (NH) | 3/4" | FBSO100F-PG |
| 1-1/2" | | 1" | FBSO150F-PG |



Ball Shutoff Nozzle Tips

Size

- 1/2" orifice standard; other sizes available, contact Dixon®

Feature

- Lightweight

Specification

- Maximum operating pressure: **200 PSI** (water only) at ambient temperature **70°F (21°C)**

| Size | Thread | Length | Orifice | Anodized Aluminum Part # |
|--------|----------|--------|---------|--------------------------|
| 1" | NPSH | 4" | 1/2" | ANT100 |
| 1-1/2" | | 4-3/4" | | ANT150 |
| 1" | NST (NH) | 4" | | ANT100F |
| 1-1/2" | | 4-3/4" | | ANT150F |



NPSH



NST

NOTE: Gaskets are special order, please call 877.712.6179 for assistance.