


## Global Air King®

### Features

- Supplied with safety clip and rubber washers
- Use with Boss® clamps; see pages 161 - 162
- Not to be used for steam service 
- Must use safety clips, safety clips are same size for both 2-lug and 4-lug Air King couplings, see page 186

### Specification

- Pressure rating: 150 PSI at ambient temperature 70°F (21°C)

### 2-Lug Hose Ends



| Size | Plated Steel Part # | Pkg Qty |
|------|---------------------|---------|
| 1/2" | GAM1                | 25      |
| 3/4" | GAM6                | 50      |
| 1"   | GAM11               | 50      |

### 2-Lug Male NPT Ends



| Size | Plated Steel Part # | Pkg Qty |
|------|---------------------|---------|
| 1/2" | GAM2                | 25      |
| 3/4" | GAM7                | 50      |
| 1"   | GAM12               | 50      |

### 2-Lug Female NPT Ends



| Size | Plated Steel Part # | Optional Qty |
|------|---------------------|--------------|
| 1/2" | GAM3                | 25           |
| 3/4" | GAM8                | 50           |
| 1"   | GAM13               | 50           |

### 2-Lug Blank End




| Plated Steel Part # | Optional Qty |
|---------------------|--------------|
| GAM0                | 25           |

### 2-Lug Triple Connection



| Plated Steel Part # | Optional Qty |
|---------------------|--------------|
| GAM10               | 25           |

NOTE: Air King is for air and water service only. Warning: Never use any Air King coupling for steam service! None of Dixon's catalog information is to be interpreted to mean that this type of coupling is suitable for use on steam hose. 

E