

## Series 1 FRLs


### F07-Series Carded Miniature Filters

#### Features

- 5 micron element
- 1 oz. reservoir
- Transparent bowl

#### Specifications

- Inlet pressure 150 PSI maximum
- Maximum temperature: 125°F (52°C)



Port Size	Flow (SCFM)	Automatic Drain Part #	Manual Drain Part #
1/4"	24	F07-200AC	F07-200MC




### R07-Series Carded Miniature Regulator

#### Features

- Relieving type
- Supplied with a GC620 gauge

#### Specifications

- Inlet pressure 250 PSI maximum
- Maximum temperature: 150°F (66°C)
- Pressure range 5-100 PSI



Port Size	Flow (SCFM)	with Gauge Part #
1/4"	15	R07-200RGC




### L07-Series Carded Miniature Lubricator

#### Feature

- 1 oz. reservoir

#### Specifications

- Inlet pressure 150 PSI maximum
- Maximum temperature: 125°F (52°C)



Port Size	Flow (SCFM)	with Transparent Bowl Part #
1/4"	14	L07-200AC




### B07-Series Carded Miniature Filter/Regulators

#### Features

- Relieving type
- 5 micron element
- 1 oz. reservoir
- Push-to-lock adjusting knob
- Supplied with a GC620 gauge
- Bowl guard not available
- Transparent bowl

#### Specifications

- Pressure range 5-100 PSI
- Inlet pressure 150 PSI maximum
- Maximum temperature: 125°F (52°C)



Port Size	Flow (SCFM)	Automatic Drain Part #	Manual Drain Part #
1/4"	14	B07-202AGC	B07-202MGC



NOTE: FRLs are designed for air service only, unless otherwise indicated. SCFM ratings given at 150 PSIG inlet pressure. SCFM ratings given at 100 PSIG inlet pressure for regulators, 90 PSIG all others.