



Sanitary 3½" Pressure Gauges

Features:

- accuracy: ± 1.5% of full scale
- over range capacity: 30%
- wetted surfaces: 316L stainless steel
- surface finishes (wetted parts): R_a max = 25 microinches
- case material: 304 stainless steel
- dial size: 3½"
- lens material: polycarbonate
- temperature range: 0°F (-18°C) to 250°F (121°C)
- standard fill: food grade glycerin
- rezero feature: standard on pointer
- shipping weight: approximately 3 lbs. (1.3 kg)

Sanitary Fittings



Dial Size	Clamp Size	Pressure Range (PSI)	Mount	316L Stainless Steel Part #
3½"	1½"	0-30	bottom	3S-B-15U-GFBTSS
	1½"	0-60	bottom	3S-C-15U-GFBTSS
	1½"	0-100	bottom	3S-D-15U-GFBTSS
	1½"	0-160	bottom	3S-E-15U-GFBTSS
	1½"	0-200	bottom	3S-F-15U-GFBTSS
	1½"	0-300	bottom	3S-G-15U-GFBTSS
	1½"	0-30	back	3S-B-15U-GFBKSS
	1½"	0-60	back	3S-C-15U-GFBKSS
	1½"	0-100	back	3S-D-15U-GFBKSS
	1½"	0-160	back	3S-E-15U-GFBKSS
	1½"	0-200	back	3S-F-15U-GFBKSS
	1½"	0-300	back	3S-G-15U-GFBKSS
	2"	0-30	bottom	3S-B-2U-GFBTSS
	2"	0-60	bottom	3S-C-2U-GFBTSS
	2"	0-100	bottom	3S-D-2U-GFBTSS
	2"	0-160	bottom	3S-E-2U-GFBTSS
	2"	0-200	bottom	3S-F-2U-GFBTSS
	2"	0-300	bottom	3S-G-2U-GFBTSS
	2"	0-30	back	3S-B-2U-GFBKSS
	2"	0-60	back	3S-C-2U-GFBKSS
	2"	0-100	back	3S-D-2U-GFBKSS
	2"	0-160	back	3S-E-2U-GFBKSS
	2"	0-200	back	3S-F-2U-GFBKSS
	2"	0-300	back	3S-G-2U-GFBKSS