

FSA-Storz x Rigid Female

Features:

- for use wherever a non-valved, locking coupling is required
- anodized components per MIL-A-8625 Type III Class 1
- Buna-N gaskets
- working pressure: **150 PSI at 70°F (21°C)**
- cast aluminum lock lever assembly on 4", 5" and 6"

Storz x NST (NH) Female

Storz Size	NST (NH) Female Thread	6061-T6 Forged Aluminum Part #
1½"	1½"	<b>FSA1515F</b>
2"	1½"	<b>FSA2015F</b>
	2½"	<b>FSA2025F</b>
2½"	2½"	<b>FSA2525F</b>
	3"	<b>FSA3025F</b>
4"	2½"	<b>FSA4025F</b>
	3"	<b>FSA4030F</b>
	4"	<b>FSA4040F</b>
	4½"	<b>FSA4045F</b>
	5"	<b>FSA4050F</b>
	6"	<b>FSA4060F</b>
5"	2½"	<b>FSA5025F</b>
	3"	<b>FSA5030F</b>
	4"	<b>FSA5040F</b>
	4½"	<b>FSA5045F</b>
	5"	<b>FSA5050F</b>
6"	6"	<b>FSA5060F</b>
	6"	<b>FSA6060F</b>



Storz x NPT Female

Storz Size	NPT Female Thread	6061-T6 Forged Aluminum Part #
1½"	1"	<b>FSA1510T</b>
	1½"	<b>FSA1515T</b>
2"	1½"	<b>FSA2015T</b>
	2"	<b>FSA2020T</b>
2½"	1½"	<b>FSA2515T</b>
	2"	<b>FSA2520T</b>
	2½"	<b>FSA2525T</b>
	3"	<b>FSA2530T</b>
3"	3"	<b>FSA3030T</b>
	3"	<b>FSA4030T</b>
	4"	<b>FSA4040T</b>
4"	6"	<b>FSA4060T</b>
	3"	<b>FSA5030T</b>
	4"	<b>FSA5040T</b>
5"	5"	<b>FSA5050T</b>
	6"	<b>FSA5060T</b>
	4"	<b>FSA6040T</b>
6"	6"	<b>FSA6060T</b>



Storz x NPSH Female

Storz Size	NPSH Female Thread	6061-T6 Forged Aluminum Part #
1½"	1½"	<b>FSA1515S</b>
2"	1½"	<b>FSA2015S</b>
2½"	2½"	<b>FSA2525S</b>
4"	4"	<b>FSA4040S</b>



- All adapters are made to approved Dixon® specifications.
- Replacement washers can be found on page 798