


### American Made PTFE Tape (Purple)

**Features:**

- thickness: 3.5 mil (0.0035 mm)
- temperature range: **-450°F to 500°F (-268°C to 260°C)**
- superior quality
- not for use in oxygen applications 




Size	Length	Part #
1/2"	520"	<b>TTPM50-520</b>
	700"	<b>TTPM50-700</b>
	1429"	<b>TTPM50-1429</b>
3/4"	520"	<b>TTPM75-520</b>
	700"	<b>TTPM75-700</b>
	1429"	<b>TTPM75-1429</b>
1"	520"	<b>TTPM100-520</b>
	700"	<b>TTPM100-700</b>
	1429"	<b>TTPM100-1429</b>

### Industrial PTFE Tape (White)

**Features:**

- thickness: 3.5 mil (0.0035 mm)
- temperature range: **-212°F to 500°F (-136°C to 260°C)**



Size	Length	Part #	Optional Qty
1/2"	260"	<b>TTA50</b>	550
	520"	<b>TTB50</b>	500
	1296"	<b>TTC50</b>	250
3/4"	260"	<b>TTA75</b>	350
	520"	<b>TTB75</b>	350
1"	520"	<b>TTB100</b>	250

### Stainless Steel PTFE Tape (Gray)

**Features:**

- thickness: 4 mil
- temperature range: **-450°F to 550°F (-268°C to 288°C)**
- useful on stainless steel threaded joints or connections
- PTFE with nickel added, nickel acts like a ball bearing
- made in the US



Size	Length	Part #	Optional Qty
1/2"	260"	<b>TTA50SS</b>	10

### Industrial Heavy Duty PTFE Tape (Pink)

**Features:**

- thickness: 4 mil
- temperature range: **-400°F to 500°F (-240°C to 260°C)**



Size	Length	Part #	Optional Qty
1/2"	540"	<b>TTBP50</b>	500

### PTFE Tape for LP Gas (Yellow)

**Features:**

- thickness: 4 mil
- maximum temperature: **500°F (260°C)**
- Underwriters Listed 



Size	Length	Part #	Optional Qty
1/2"	260"	<b>TTA50LP</b>	500